

THERMOPOLIS DEMOLITION DERBY

2017 OUTLAW CLASS

CAR MUST BE SEDAN OR WAGON.

CAR MUST BE COMPLETELY STRIPPED DOWN.

ANY REINFORCEMENTS TO FRAME AND BODY ARE ALLOWED.

FABRICATED/ STUFFED BUMPERS ARE ALLOWED.

ANY REAR AXLE IS PERMITTED, WITH ANY LUG PATTERN.

ANY TIRE AND/OR RIM (INCLUDING BEADLOCK) IS PERMITTED.

DOUBLING AND FORM FILLING IS HIGHLY RECOMMENDED TO AVOID FLATS.

MANDATORY SAFETY REQUIREMENTS ARE AS FOLLOWS:

I. Safety

A. Drivers Door **MUST** be **WELDED** and **REINFORCED** for driver safety.

II. Driver Safety Equipment

A. All drivers **MUST** wear closed-toe shoes and pants. Shorts/sandals will **NOT** be permitted.

B. Long sleeved shirts and gloves are recommended. The use of *fire-retardant clothing* is **HIGHLY RECOMMENDED**.

C. A DOT approved closed faced safety helmet is **MANDATORY**. If this equipment falls off during the derby- you may be **DISQUALIFIED**. *Face shields, goggles, or safety glasses* are **HIGHLY RECOMMENDED**.

D. At minimum, a lap-safety belt is **MANDATORY**. If a safety belt becomes unsecured during the derby, **DRIVER MAY BE DISQUALIFIED**. *A shoulder harness* is **HIGHLY RECOMMENDED**.

E. Fire extinguishers are optional. If used, they **MUST** be mounted **SECURELY**.

F. **MUST HAVE AT LEAST A 4-POINT CAGE FOR SAFETY!** The 4-point cage **MUST** be constructed with **AT LEAST** (4) vertical posts, (1) bar across the dash area, and (1) bar across the rear seat area.

G. Halo Bars- **MANDATORY**- Halo bar may be mounted inside or over the roof of the vehicle.

III. Fuel Systems

A. **ALL PUMP GAS ONLY!** Premium or lesser octane- **NO** alcohol fuel will be allowed.

B. All stock, factory gas tanks **MUST** be removed. *The only exception* to this rule is vehicles that have the fuel tank integrated into the trunk floor. These tanks **MUST** have holes punched through them.

C. Fuel tanks with maximum capacity of 6 gallons must be located in the rear seat area. They must be effectively secured and fastened with bolts or weld straps. Bungee or ratchet straps will **NOT** be allowed.

D. Fuel tank fittings must be secured into the tank in an appropriate fashion (**NO DUCT TAPE**).

IV. Electrical Systems

A. Batteries **MUST** be secure and **MUST** be covered for driver safety.

B. Metal battery boxes with top strap are **HIGHLY RECOMMENDED** and may be bolted or welded to the floor.

V. Brake Systems

A. All vehicles **MUST** have sufficient brakes. Drivers will be asked to demonstrate braking ability during inspection.

VI. Engines

A. Firewalls and floorboards may be trimmed or bent for engine and/or distributor clearance but *every attempt must be made* to close off the interior of the vehicle from the engine compartment for driver safety. Openings larger than 6" **MUST** be covered with **SHEET METAL!**

B. **NO OPEN CARBURETORS.**